

Space Only Exhibitor Information

Table of contents

Space Only Exhibitor Information

Space Only - a definition

Submission of plans & paperwork

Complex stands

Height limits

Design & build rules

Columns

Contractors - appointment of

Link to ESSA

Travel distance

Doors

Gangways

Hot works permit

Platform flooring & ramps

Stand Construction Including Dressing Methods & Materials

Stand construction general information

Fabrics, drapes, curtains & hangings

Painting and Decorating

Plastics

Timber Wood

Decorative Materials including Wallpaper & Artificial Plants

Glazing

Upholstery

Flooring

Night Sheets

Rigging



Space Only - a definition

- A Space Only stand is a marked out area on the hall floor on which your stand can be built
- There is no stand, walls, floorcovering, electrics or furniture provided. The exhibitor is responsible for providing these
- The exhibitor may build a stand themselves or appoint a contractor to do this on their behalf

Submission of plans & paperwork

All space only exhibitors will need to submit the following information

- 1. Complete the compulsory space only form
- 2. Stand plans clearly showing elevation and plan views with all measurements and dimensions noted; to include height, position of any AV, walling, major exhibits, platforms etc. Plans must clearly show the orientation of the stand within the hall
- 3. Stand build material information (if not included on your plans) and confirmation of compliance with e-guide regulations
- 4. A specific risk assessment covering the build up and breakdown of the stand
- 5. A method statement covering the build up and breakdown of the stand
- 6. A construction phase plan as your individual stand area is classed as a construction site in it's own right
- 7. Public Liability Insurance which covers the company building and dismantling your stand
- 8. If your stand is complex (see below) you must also submit structural calculations and construction drawings

The information can be submitted using the following link

- www.krmsafety.co.uk/exhibitor/login. The email required to access your area on this site is the one that was originally used to book the stand at the event.

The deadline for stand plan submissions is <u>17 October 2025</u>. We cannot guarantee to be able to process plans submitted after this date.

All plans and documentation must be submitted in English and must clearly state the exhibiting company's name & stand number and the name and contact number of the responsible contractor. All drawings must show the scale used, which should be no less than 1:50.

After submitting your plans you will receive either written questions and comments about your plans or a Permission to Commence Build Notice. Please ensure you respond promptly to any questions to ensure that we are able to issue your Permission to Commence Build Notice. Work may not commence on your stand until you have received this.

Once you have received the Permission to Commence Build Notice you should not alter the design of your stand. If you do need to change your design you must resubmit your plans for consideration.

For any queries please contact

KRM Auditing Team -T +44 (0) 1634 790332

E: standaudits@krmsafety.management



Complex stands

Should your stand be deemed to be complex the show's structural engineer will need to be appointed to review your stand design and accompanying structural information / calculations.

Complex stands can be defined as follows (please note that this is not an exhaustive list) -

- Any structure, regardless of its height, which requires structural calculations
- Multi-storey stands
- Any part of a stand or exhibit which exceeds 4m in height
- Custom-built/bespoke suspended structures
- Sound/lighting towers
- Staircases or steps
- Platforms and stages over 0.6m in height and all platforms and stages for public use (not including stand floor flats and platforms)

If the Stand design is complex the following must also be supplied

- Structural calculations and construction drawings
- A completed certificate of structural integrity for the design by an approved structural engineer
- The stand will also need to be inspected for final sign off on site, once built, before the exhibition is opened to the public

Note the exhibitor is liable for all charges relating to this

Height limits

Height Limit for Build

• The maximum build height is 3.9m There are some areas with obstructions please check before confirming builds

To verify the limits for your stand please contact:

KRM Auditing Team

T +44 (0) 1634 790332

E: standaudits@krmsafety.management



Daniera C. build	Linkuplan Walling		
Design & build rules	 Unbroken Walling A minimum of 50% of any open side must remain fully open; open sides may not be entirely blocked off Walling over 5m in length must be set back by 1m from the stand edge and have some form of visual break (at least 1m in length) such as glazed panels / planting etc Please ensure that your stand does not visually block neighbouring stands off from the rest 		
	of the exhibition		
	Walling that adjoins another stand		
	Exhibitors on blocks must provide walls between themselves and their neighbours on the block, as well as between themselves and any venue walls		
	 Neighbouring exhibitors can liaise with one another to ensure that at least one of them is building a wall or to arrange to share the cost 		
	Where you are building your own wall, the back of this must be dressed in a neutral colour without logos or graphics from the top of the wall to 2.45m off the hall floor		
	 All divides must be a minimum of 2.45m tall, built on the dividing line and run for the entire length of the enclosed side(s) 		
	 Please note: receiving a 'Permission to Commence Build Notice' does not mean that adjoining stand plans have been checked for compatibility 		
	<u>General</u>		
	 All stand construction must be completely self-supporting Any construction that backs onto a gangway must be finished on the reverse 		
	 Any construction that backs onto a gangway must be finished on the reverse Bridging of gangways is NOT permitted 		
	 The name and stand number of the company exhibiting must be prominently displayed, ensuring visibility on each open side of the stand 		
	 All stands should be designed and built in line with the <u>eGuide</u>, Venue and Organiser regulations 		
Damage / fixing	You are not permitted to fix to the fabric of the building in any way		
to the hall	 Exhibitors will be charged for making good any damages to the hall such as paint marks, tape, bolts etc 		
Columns	Where columns fall fully or partially within the area of the allocated space, they may be encased by the exhibitor on all four sides.		
	The casing must be self-supporting and may not be fastened to the column. Only the faces of the casings (not the column) which fall within the allotted space may be used for display or graphics or other pictoral matter.		
Contractors - appointment of	Space only exhibitors are free to appoint stand designers and construction contractors of their choice; for advice please call Event Supplier and Services Association (ESSA). ESSA members have been approved by ESSA and understand all UK regulations.		
Link to ESSA			
Travel distance	 The maximum travel distance from any part of the stand to a gangway shall not exceed 50m 		
	 Where there is only one means of escape from the stand this must be reduced to 20m In either case, the maximum travel distance should be reduced by 25% where alcohol is being served 		



Doors	 If you are building a storeroom /office, doors must have a minimum clear width of 800mm; however it is recommended that double doors are used for at least one of the exits in order to accommodate larger types of wheelchair Doors must have a vision panel with a zone of visibility of between 500mm and 1500mm above the floor. The exception to this is doors to small storerooms, where a small panel may suffice A suitable exit sign must be positioned above each doorway 			
	 Doors should open outwards in the direction of escape and be suitably recessed so they do not protrude into gangways 			
Gangways	Bridging of the gangways is NOT permitted.			
	Gangways must be kept clear at all times, including build up and breakdown. Please request advice from the Floor Manager when looking at the most suitable location for you to work from.			
Hot works permit	Hot works are not permitted without express permission of the organisers.			
Platform flooring & ramps	The use of platforms should be avoided where possible, in order to provide a level access to exhibits and services. Where the use of platforms is unavoidable, they should not exceed 170mm in height and ramped access should be provided. For further guidance, please refer to the <u>eGuide</u> .			
Stand Cons	truction Including Dressing Methods & Materials			
Stand construction general information	All materials fised in the construction of stands, inclination stong and tascias, shall be,			
	of a suitable nature and quality for the purposes and conditions of their intended use			

- adequately prepared and fixed in order adequately to perform the functions for which they are designed
- non-combustible, inherently non-flammable or durably flameproof in accordance with British standard numbers BS476 and BS5570 and/or BS3120
- Water-based, where applicable, e.g. adhesives and paint
- British Standards are the minimum acceptable standards for construction materials.
 Suitable samples of materials may be submitted to the venue for approval. Materials may be tested on site to ensure that they comply

Your stand will be inspected during build-up and the Fire Safety Officer may remove any offending materials, or close down a stand if it does not comply with fire regulations.

Fabrics, drapes, curtains & hangings

- Drapes, curtains, hangings, etc, must be inherently or durably flameproofed. Otherwise they may be treated with a proprietary flame retardant. Test certificates must be available for inspection for any materials intended to be used.
- Textile fabrics used for interior decorating of stands should be fixed taut and/or in tight pleats (not draped) to a solid backing secured above floor level and not touching light fittings.
- Curtains on exit routes should hang 75mm clear of the floor be parted in the centre and not conceal any exit signs



Painting and Decorating	 Only water-based paint may be used on site. The use of lead based paints and primers must be avoided. Cellulose paints are flammable and must not be used in stand dressing. If paint-spraying equipment is to be used, the method must be approved by the venue and not cause a nuisance to others. Protective measures shall be taken to ensure that no paint is spilt or sprayed on to the fabric of the building. Barrier creams and masks must be used. Painters must not work in confined areas unless adequate ventilation is available. All waste products must be disposed of properly
Plastics	 Plastics must conform to BS476 - part 7- Class 1 Perspex is not permitted to be used at this venue for stand-fitting purposes, including displays; an alternative polycarbonate, conforming to BS476 part 7 (class 1) must be used instead
Timber Wood	 Timber under 25mm thick must be impregnated to Class 1 standard. Treated materials should have 'BS 476-Part 7, Class 1' marked on them. Boards, plywood, chipboard etc. must be treated if under 18mm thick. The exception to this is MDF, which is acceptable for use due to its density. MDF and chipboard must not be machined on site, as the dust produced is hazardous to health. Chipboard must not be used as a weight-bearing material
Decorative Materials including Wallpaper & Artificial Plants	 Decorative materials used for stand dressing must be flame proofed or purchased already treated by use of the appropriate chemical. Untreated wallpaper and similar thin surface finishes, not exceeding 1mm in thickness, may be accepted, provided they are firmly fixed. Artificial plants and flowers are combustible and give off toxic fumes. Therefore, they must not be used for stand dressing. Silk-type flowers are acceptable, providing they are fireproof or have been treated and marked as such.



Glazing	dots, logos, etc. Overhead glazing protected from shall glazing used in tempered) a mining Areas of glazing with dimension of the	d, large areas of clear glazing shall be indicated with warning stripes, shall be of wired or laminated glass or be otherwise adequately nattering. In the construction of stands must consist of safety glass (laminated or mum of 6mm thick. Within 800mm of floor level and over 0.5m2, where the smaller pane is greater than 250mm, must conform to the thicknesses shown of comply with the 'Code of practice for safety related to human	
	impact'. Nominal thickness	Maximum pane size dimensions	
	8mm	1100mm x 1100mm	
	10mm	2250mm x 2250mm	
	12mm	4500mm x 4500mm	
	15mm or thicker	no limits	
Upholstery	appropriate stand		
Flooring	 Space only stands are required to provide their own floor covering and ensure that it is removed and disposed of at the end of the event. All floor covering must be suitable for its purpose and security fixed using approved fixing tape. Cables must be hidden away, located out of main walkways and securely fixed down and ramped if required so that they do not present a trip hazard. 		
Night Sheets	 Night sheets must be made of inherently non-flammable material or of material satisfactorily treated to render it non-flammable. They must be stored rolled-up and firmly secured and not cause any obstruction while not in use. 		
Rigging	 If you wish to have banners or other rigging on your stand, you must obtain permission from the organisers. All rigging attachments must be made using approved Rigging personnel; Please contact angela@waysandmeansevents.com for approval and information 		